

ENVIRONMENTAL PRODUCT DECLARATION

In accordance with ISO 14025:2006 and
EN 15804:2012+A2:2019/AC:2021 for:



The International EPD® System
Programme operator: EPD International AB
Registration number: EPD-IES-0033145:001



An EPD may be updated or republished if
conditions change. To find the latest version
of the EPD and to confirm its validity, see:
www.environdec.com

webersan thermo evoluzione

Version 1

Version date: 2026/07/07

Validity: 5 years

Validity date: 2031/07/06



Weber, Saint-Gobain

GENERAL INFORMATION

Programme information

PROGRAMME:	The International EPD® System
ADDRESS:	EPD International AB - Box 210 60 - SE-100 31 Stockholm – Sweden
WEBSITE:	www.environdec.com
E-MAIL:	support@environdec.com

PCR information

Product Category rules (PCR)

CEN standard EN 15804:2012+A2:2019/AC:2021 as the Core Product Category Rules (PCR)

Product category rules (PCR): PCR 2019:14 Construction Products, version 2.0.1

PCR review was conducted by: The Technical Committee of the International EPD® System

See www.environdec.com for a list of members.

C-PCR: c-PCR-003 Concrete and concrete elements (EN 16757: 2017)

Chairs of the PCR review: Rob Rouwette (chair), Noa Meron (co-chair).

Verification

External and independent ('third-party') verification of the declaration and data, according to ISO 14025:2006, via

EPD verification through:

- ☒ Individual EPD verification without a pre-verified LCA/EPD tool
- ☐ Individual EPD verification with a pre-verified LCA/EPD tool
- ☐ EPD process certification* without a pre-verified LCA/EPD tool
- ☐ EPD process certification* with a pre-verified LCA/EPD tool
- ☐ Fully pre-verified EPD tool

Independent third-party verification of the declaration and data, according to ISO 14025:2006:

Third party verifier: Certiquality Srl | Via G. Giardino, 4 – 20123 Milano – IT

info@certiquality.it | certiquality.it

Approved by: Accredia 0027VV

C-PCR : c-PCR-003 Concrete and concrete elements (EN 16757: 2017)

Approved by: The International EPD® System

Procedure for follow-up of data during EPD validity involves third part verifier: ☐ Yes ☒ No

Ownership and limitation on use of EPD

The EPD owner has the sole ownership, liability and responsibility for the EPD.

EPDs within the same product category but published in different EPD programmes, may not be comparable. For two EPDs to be comparable, they shall be based on the same PCR (including the same first-digit version number) or be based on fully aligned PCRs or versions of PCRs; cover products with identical functions, technical performances and use (e.g. identical declared/functional units); have identical scope in terms of included life-cycle stages (unless the excluded life-cycle stage is demonstrated to be insignificant); apply identical impact assessment methods (including the same version of characterization factors); and be valid at the time of comparison.

Information about EPD Owner

Address and contact information about the EPD owner:

SAINT-GOBAIN ITALIA S.P.A

Via Giovanni Bensi 8, 20152 Milano, (Italy)

Tel. (+39) 02 611151/ mail: sg.ppc@legalmail.it / web: <https://www.saint-gobain.it/>

Description of the organization of the EPD owner:

At Weber, we believe that the most important aspect of the construction industry is caring for people and their environment. Weber develops, produces, and sells solutions based on industrial mortars and construction chemicals for building and renovation projects.

Weber is made up of 10,000 people across 64 countries, supported by nearly 200 production units.

Weber's services and solutions are designed to help customers save time, feel safe and comfortable, succeed in their work, and grow their business.

Our brand promises:

Well-being: We care about everyone's safety and benefit. Making life easier, more convenient, and more comfortable.

Empathy: We care about people. Listening to what matters to them and considering their needs. Helping everyone grow. Responding to the many challenges of today's world and adapting to the diversity of the lives within it.

Sustainability over time: We care about the present, but also about the future. Taking responsibility to lead change and build a tomorrow that is in harmony with its environment.

Weber, a Saint-Gobain brand:

Saint-Gobain designs, manufactures, and distributes materials and solutions that are key ingredients for the well-being of each of us and the future of all. They are found everywhere we live and in our daily lives: in buildings, transportation, infrastructure, and many industrial applications, providing comfort, performance, and safety.

Management system-related certification:

ISO 9001 "Quality management systems"

ISO 14001 "Environmental management systems"

ISO 45001 "Occupational health and safety management systems"

LCA practitioner: Riccardo Bertino, riccardo.bertino@saint-gobain.com

Communication: The intended use of this EPD is for B2B communication.

Product information

Product name: webersan thermo evoluzione

Visual representation of the product:

UN CPC CODE: 37510 Non-refractory mortars and concretes

Manufacturing site(s):

Montiglio: Via della Repubblica, 9, 14026 Montiglio Monferrato (AT), Italy



Product description

The product webersan thermo evoluzione is a white, single-component, lightweight plaster designed for thermal insulation and the restoration of damp and saline masonry deteriorated by rising capillary damp. It can be used both indoors and outdoors on brick, mixed stone, and concrete masonry.

For more information:

<https://www.it.weber/prodotti/rasanti-intonaci-finiture-risanamento/intonaci-e-finiture-risanamento-muratura-umida/intonaci-da-risanamento/webersan-thermo-evoluzione>

All figures in this EPD refers to webersan thermo evoluzione

Description	Value	Unit
webersan thermo evoluzione	1	Kg / DU
Lifespan	50	Years

Technical data/physical characteristics:

Parameter	Value / Description	
Reaction to fire	A1	EN 13501-1
Installation information (kg/m ²)	18	
Compressive strength 28 days	3 MPa	EN 998-1
Thermal conductivity	λ : 0,11 W/mK	EN 7745:1977
Water vapor permeability	μ = 9	EN 998-1
Water absorption	W1	EN 998-1
Entrapped air (dry)	> 35%	EN 998-1

Content declaration

Description of the main components and/or materials:

Product components	Weight (kg)	Post-consumer recycled material weight (%)	Biogenic material, weight- %	Biogenic material, kg C/kg of DU
Binder	30 – 40 %	0%	0 %	0 kg
Minerals	50 – 60 %	0%	0 %	0 kg
Additives	1 – 2 %	0%	0,25 %	0,025 kg
Sum	100% = 1 kg	0%	0,25%	0,025 kg
Packaging materials	Weight (kg)	Weight versus the product (%)	Weight biogenic carbon, kg C/kg product	Biogenic material, kg C/kg of DU
Composite bag (85% paper +15% LDPE)	0,0059	0,059 %	2,17E-03	2,17E-03
Polyethylene film (LDPE)	0,000838	0,00838 %	0	0

Hazardous substances

At the date of issue of this declaration, there is no “Substance of Very High Concern” (SVHC) in concentration above 0.1% by weight, and neither do their packaging, following the European REACH regulation (Registration, Evaluation, Authorization and Restriction of Chemicals).

LCA information

TYPE OF EPD	Cradle to gate with options, module C1-C4, module D and optional modules (A4–A5 + B1–B7).
DECLARED UNIT	1 kg of dry powder with packaging
SYSTEM BOUNDARIES	Cradle to gate with options, module C1-C4, module D and optional modules (A4–A5 + B1–B7).
REFERENCE SERVICE LIFE (RSL)	The Reference Service Life (RSL) of the mortar product is 50 years. This 50-year value is the amount of time that we recommend our products last for without refurbishment and corresponds to standard building design life.
CUT-OFF RULES	In the case that there is not enough information, the process energy and materials representing less than 1% of the whole energy and mass used can be excluded (if they do not cause significant impacts). The addition of all the inputs and outputs excluded cannot be bigger than the 5% of the whole mass and energy used, as well of the emissions to environment occurred. Flows related to human activities such as employee transport are excluded. The construction of plants, production of machines and transportation systems are excluded since the related flows are supposed to be negligible compared to the production of the building product when compared at these systems lifetime level.
ALLOCATIONS	Allocation has been avoided when possible and when not possible a mass allocation has been applied. The polluter pays and the modularity principles as well have been followed.
DATA QUALITY ASSESSMENT	Data quality of primary and secondary data had been judged by its precision (measured, calculated, or estimated), completeness (e.g., unreported emissions), consistency (degree of uniformity of the methodology applied), and representativeness (geographical, technological, and temporal).
GEOGRAPHICAL COVERAGE AND TIME PERIOD	Scope: Italy Data is collected from 1 production site Montiglio located in Italy Data collected for the year 2025
BACKGROUND DATA SOURCE	The databases Sphera CUP2024.2 and ecoinvent v.3.10 EF Package 3.1
SOFTWARE	Sphera LCA for experts (GaBi) 10

Data quality declaration

Data Collection	01/01/2025 to 31/12/2025
Sites used	Montiglio
Geography	Produce in "Italy" Sold in Italy" Use and disposal in Italy"
Technology	Mortars are produced by mixing cement, others minerals and some additives.
Averaging	Production in one plant covering 100 % of production by the company
LCI/LCA database	Sphera CUP2024.2 and ecoinvent v.3.10
EPD used	No specific EPDs of raw materials are used
Data Quality Scheme	EN 15804:2012+A2:2019, Annex E, Table E.2
Use of Fair data with more than 30 % of a core impact	None
Use of Poor relevant data	None
Use of Very Poor relevant data	None

Process	Source type	Source	Reference year	Data category	A1-A3 GWP-GHG [kg CO2 eq.]
Manufacturing process					
Energy Primary	Database	Sphera 2024.2	<5 years old	Primary data	4 %
Transportation (only if Primary data collected)					
A2_Transport_Primary	Database	Sphera 2024.2 /ecoinvent 3.10	<5 years old	Primary data	2,5 %
Background datasets in A1-A3					
Other processes	Database	Sphera 2024.2 /ecoinvent 3.10	<5 years old	Secondary data	93,5%
Total share of primary data					6,5 %


A1-A3 GWP-GHG [kg CO2 eq.]	4,63E-01
-----------------------------------	----------

Description of system boundaries

System boundaries (X=included. MND=module not declared)

	PRODUCT STAGE			CONSTRUCTION STAGE		USE STAGE							END OF LIFE STAGE				BENEFITS AND LOADS BEYOND THE SYSTEM BOUNDARY
	Raw material supply	Transport	Manufacturing	Transport	Construction-Installation process	Use	Maintenance	Repair	Replacement	Refurbishment	Operational energy use	Operational water use	De-construction demolition	Transport	Waste processing	Disposal	Reuse-recovery
Module	A1	A2	A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
Modules declared	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X
Geography	IT	IT	IT	IT	IT	IT	-	-	-	-	-	-	IT	IT	IT	IT	IT

System boundaries when the end-of-waste state is reached:



(*)As defined by EN15804+A2

Life cycle stages

A1-A3. Product stage

The product stage of plaster products is subdivided into 3 modules A1, A2 and A3 respectively “raw material supply”, “transport to manufacturer” and “manufacturing”.

A1. Raw materials supply

This module includes the extraction and transformation of raw materials.


A2. Transport to the manufacturer

This module includes the transportation of raw materials and packaging to the manufacturing site. The modelling includes road, boat and/or train transportations.

A3. Manufacturing

This module includes the manufacture of products and the manufacture of packaging. The production of packaging material is considered at this stage. The processing of any waste arising from this stage is also included.

Manufacturing process flow diagram



The manufacturing activities include grinding, drying, storing, mixing, packing and internal transportation. Packaging-related flows in the production process and all up-stream packaging are included in the manufacturing module, i.e., wooden pallets, bags, and LDPE film.

A4-A5. Construction process stage

The construction process is divided into 2 modules: A4, Transport to the building site and A5, Installation in the building.

A4. Transport to the building site

This module includes transport from the production gate to the building site. Transport is calculated based on a scenario with the parameters described in the following table.

PARAMETER	VALUE
Fuel type and consumption of vehicle or vehicle type used for transport e.g. long-distance truck, boat, etc.	Freight truck trailer 24 t payload, diesel consumption 38 liters for 100 km
Distance	650 km
Capacity utilisation (including empty returns)	68,4% of the capacity in mass 30% of empty returns
Bulk density of transported products*	750 kg / m ³
Volume capacity utilisation factor	1 (by default)

A5. Installation in the building

This module includes: the installation of the product, the surplus of raw materials and packaging (cradle to gate) to compensate for the loss of product during the installation, the transport and management of packaging and product waste.

In this module was taken into consideration:

- Energy used in the equipment to prepare the product.

Not taken into consideration:

- Additional accessories for installation
- Energy used to install the product (manual tools are used instead).

PARAMETER	VALUE / DESCRIPTION
Ancillary materials for installation (specified by materials)	none
Water use	0.50 liters/kg of dry mortar
Other resource use	None
Quantitative description of energy type (regional mix) and consumption during the installation process	0.0396 MJ/kg of dry mortar
Wastage of materials on the building site before waste processing, generated by the product's installation (specified by type)	5% losses during installation
Output materials (specified by type) as results of waste processing at the building site e.g. of collection for recycling, for energy recovering, disposal	Product waste: 0,05 kg mortar (landfill) Packaging waste: Composite bag (paper - LDPE):0,0059 kg to landfill Low-density polyethylene (LDPE) film: 0,000838 kg to landfill Wooden pallet: 0,0016 kg to landfill Wooden pallet: 0,011 kg is reused
Direct emissions to ambient air, soil, and water	None

B1-B7. Use stage (excluding potential savings)

The use stage is divided into the following modules:

- **B1**
 - Potential carbonation is calculated according to the methodology proposed in the c-PCR-003 Concrete and concrete elements (EN 16757).
- **B2: Maintenance**
- **B3: Repair**
- **B4: Replacement**
- **B5: Refurbishment**
- **B6: Operational energy use**
- **B7: Operational water use**

The product has a reference service life of 50 years. This assumes that the product will last in situ with no requirements for maintenance, repair, replacement, or refurbishment throughout this period. Therefore, it has no impact at this stage.

C1-C4. End of Life Stage

This stage includes the next modules:

- **C1: Deconstruction, demolition.** The de-construction and/or dismantling of the product take part of the demolition of the entire building. The energy considered for demolition is 0.018 MJ/kg.
- **C2: Transport to waste processing**
- **C3: Waste processing for reuse, recovery and/or recycling**
- **C4: Waste disposal**, including physical pre-treatment and site management.
-

Description of the scenarios and additional technical information for the end of life:

PARAMETER	VALUE/DESCRIPTION
Collection process specified by type	1,50 kg (1 kg of dry powder + 0,50 kg of water content) collected with mixed construction waste.
Recovery system specified by type	There is no recovery, recycling or reuse of the product once it was reached its end of life phase
Disposal specified by type	100 % (1,50 kg) to municipal landfill
Assumptions for scenario development (e.g. transportation)	Average truck trailer with 27t payload, diesel consumption 38L/100km ; 100km distance to landfill

D. Reuse/recovery/recycling potential

In the module D are declared the environmental benefits and loads from reusable products, recyclable materials, or energy recovery. Module D considers:

- Inputs of secondary materials: recycled raw materials for product and packaging (pre- and post-consumer),
- Outputs of secondary materials: product and/or packaging sent to recycling,
- Exported energy (electric or thermal): product and/or packaging sent to incineration with energy recovery.

Environmental performance

As specified in EN 15804:2012+A2:2019/AC:2021 and the Product-Category Rules, the environmental impacts are declared and reported using the baseline characterization factors based on EF 3.1. Raw materials and energy consumption, as well as transport distances have been taken directly from the manufacturing plant.

The estimated impact results are only relative statements which do not indicate the end points of the impact categories, exceeding threshold values, safety margins or risks.

The results of the end-of-life stage (modules C1-C4) should be considered when using the results of the product stage (modules A1-A3)

Disclaimer 1: The results of this environmental impact indicator shall be used with care as the uncertainties on these results are high or as there is limited experienced with the following indicators:

- Resource use, mineral and metals [kg Sb eq.]
- Resource use, energy carriers [MJ]
- Water deprivation potential [m³ world equiv.]
- Land use [Pt]
- Human toxicity (cancer) [CTUh]
- Human toxicity(noncancer) [CTUh]
- Ecotoxicity (freshwater [CTUe]

Disclaimer 2: The impact category Ionizing radiation, human health [kBq U235 eq.] deals mainly with the eventual impact of low dose ionizing radiation on human health of the nuclear fuel cycle. It does not consider effects due to possible nuclear accidents, occupational exposure nor due to radioactive waste disposal in underground facilities. Potential ionizing radiation from the soil, from radon and from some construction material is also not measured by this indicator.

Disclaimer 3: The assumptions for the modules are in accordance with the project report (LCA study).

The following non-mandatory additional environmental indicators are not declared:

- Ecotoxicity freshwater [CTUe]
- Particulate Matter emissions [Disease incidence]
- Cancer human health effects [CTUh]
- Ionizing radiation - human health [kBq U235 eq.]
- Non-cancer human health effects [CTUh]
- Land Use [Pt].

Results refer to a declared unit of 1kg/kg of dry powder whit packaging.

The following results corresponds to a single product manufactured in a single plant.

Environmental Impacts

		PRODUCT STAGE	CONSTRUCTION STAGE		USE STAGE							END OF LIFE STAGE				BENEFITS AND LOADS BEYOND THE LIFE CYCLE
Environmental indicators		A1 / A2 / A3	A4 Transport	A5 Installation	B1 Use	B2 Maintenance	B3 Repair	B4 Replacement	B5 Refurbishment	B6 Operational energy use	B7 Operational water use	C1 Deconstruction / demolition	C2 Transport	C3 Waste processing	C4 Disposal	D Reuse, recovery, recycling
	Climate Change [kg CO2 eq.]	4,29E-01	4,84E-02	7,11E-02	-3,22E-02	0	0	0	0	0	0	1,89E-03	7,17E-03	0	2,78E-02	0
	Climate Change (fossil) [kg CO2 eq.]	4,59E-01	4,75E-02	3,70E-02	-3,22E-02	0	0	0	0	0	0	1,89E-03	7,04E-03	0	1,70E-02	0
	Climate Change (biogenic) [kg CO2 eq.]	-3,53E-02	1,31E-04	3,38E-02	0	0	0	0	0	0	0	1,62E-06	2,01E-05	0	1,07E-02	0
	Climate Change (land use change) [kg CO2 eq.]	4,74E-03	7,86E-04	2,96E-04	0	0	0	0	0	0	0	6,88E-08	1,17E-04	0	1,02E-04	0
	Ozone depletion [kg CFC-11 eq.]	9,94E-10	4,71E-15	7,30E-11	0	0	0	0	0	0	0	1,61E-16	1,03E-15	0	4,60E-14	0
	Acidification terrestrial and freshwater [Mole of H+ eq.]	9,14E-04	5,24E-05	8,64E-05	0	0	0	0	0	0	0	4,33E-06	9,34E-06	0	1,21E-04	0
	Eutrophication freshwater [kg P eq.]	2,40E-06	2,00E-07	7,22E-06	0	0	0	0	0	0	0	3,60E-10	2,97E-08	0	3,87E-08	0
	Eutrophication marine [kg N eq.]	3,24E-04	1,73E-05	1,44E-04	0	0	0	0	0	0	0	1,74E-06	3,37E-06	0	3,11E-05	0
	Eutrophication terrestrial [Mole of N eq.]	3,19E-03	2,11E-04	2,76E-04	0	0	0	0	0	0	0	1,91E-05	4,01E-05	0	3,43E-04	0
	Photochemical ozone formation - human health [kg NMVOC eq.]	8,71E-04	4,90E-05	7,58E-05	0	0	0	0	0	0	0	5,14E-06	9,27E-06	0	9,53E-05	0
	Resource use, mineral and metals [kg Sb eq.] ¹	3,50E-07	3,98E-09	2,79E-08	0	0	0	0	0	0	0	4,55E-11	6,06E-10	0	1,10E-09	0
	Resource use, energy carriers [MJ] ¹	3,11E+00	6,10E-01	3,75E-01	0	0	0	0	0	0	0	2,45E-02	9,17E-02	0	2,25E-01	0
	Water deprivation potential [m³ world equiv.] ¹	4,76E-02	6,96E-04	2,24E+00	0	0	0	0	0	0	0	5,13E-06	1,08E-04	0	1,95E-03	0

¹ The results of this environmental impact indicator shall be used with care as the uncertainties on these results are high or as there is limited experienced with the indicator

Resources Use

	PRODUCT STAGE	CONSTRUCTION STAGE		USE STAGE							END OF LIFE STAGE				BENEFITS AND LOADS BEYOND THE LIFE CYCLE
Resources Use indicators ²	A1 / A2 / A3	A4 Transport	A5 Installation	B1 Use	B2 Maintenance	B3 Repair	B4 Replacement	B5 Refurbishment	B6 Operational energy use	B7 Operational water use	C1 Deconstruction / demolition	C2 Transport	C3 Waste processing	C4 Disposal	D Reuse, recovery, recycling
 Use of renewable primary energy (PERE) [MJ] ³	9,00E-01	5,16E-02	8,59E-02	0	0	0	0	0	0	0	1,22E-04	7,90E-03	0	3,92E-02	0
 Primary energy resources used as raw materials (PERM) [MJ] ²	3,55E-01	0	-1,55E-01	0	0	0	0	0	0	0	0	0	0	0	0
 Total use of renewable primary energy resources (PERT) [MJ] ²	1,25E+00	5,16E-02	-6,96E-02	0	0	0	0	0	0	0	1,22E-04	7,90E-03	0	3,92E-02	0
 Use of non-renewable primary energy (PENRE) [MJ] ²	2,99E+00	6,10E-01	3,69E-01	0	0	0	0	0	0	0	2,45E-02	9,17E-02	0	2,25E-01	0
 Non-renewable primary energy resources used as raw materials (PENRM) [MJ] ²	1,18E-01	0	5,92E-03	0	0	0	0	0	0	0	0	0	0	0	0
 Total use of non-renewable primary energy resources (PENRT) [MJ] ²	3,11E+00	6,10E-01	3,75E-01	0	0	0	0	0	0	0	2,45E-02	9,17E-02	0	2,25E-01	0
 Use of secondary material (SM) [kg]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
 Use of renewable secondary fuels (RSF) [MJ]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
 Use of non-renewable secondary fuels (NRSF) [MJ]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
 Use of net fresh water (FW) [m3]	1,34E-03	5,80E-05	5,21E-02	0	0	0	0	0	0	0	1,84E-07	8,80E-06	0	5,95E-05	0

³ From EPD International Construction Product PCR 1.3.2 (Annex 3). The option B was retained to calculate the primary energy use indicators.

Waste Category & Output flows

		PRODUCT STAGE	CONSTRUCTION STAGE		USE STAGE							END OF LIFE STAGE				BENEFITS AND LOADS BEYOND THE LIFE CYCLE
Waste Category & Output Flows		A1 / A2 / A3	A4 Transport	A5 Installation	B1 Use	B2 Maintenance	B3 Repair	B4 Replacement	B5 Refurbishment	B6 Operational	B7 Operational water	C1 Deconstruction / demolition	C2 Transport	C3 Waste processing	C4 Disposal	D Reuse, recovery, recycling
	Hazardous waste disposed (HWD) [kg]	3,87E-03	1,98E-11	2,73E-04	0	0	0	0	0	0	0	7,55E-13	3,51E-12	0	5,60E-11	0
	Non-hazardous waste disposed (NHWD) [kg]	2,63E-02	9,49E-05	8,74E-02	0	0	0	0	0	0	0	5,14E-06	1,50E-05	0	1,14E+00	0
	Radioactive waste disposed (RWD) [kg]	9,59E-05	7,89E-07	1,04E-05	0	0	0	0	0	0	0	2,76E-08	1,67E-07	0	2,36E-06	0
	Components for re-use (CRU) [kg]	0	0	1,15E-02	0	0	0	0	0	0	0	0	0	0	0	0
	Materials for Recycling (MFR) [kg]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	Material for Energy Recovery (MER) [kg]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	Exported electrical energy (EEE) [MJ]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	Exported thermal energy (EET) [MJ]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0

Additional indicators from EN 15804

		PRODUCT STAGE	CONSTRUCTION STAGE		USE STAGE							END OF LIFE STAGE				BENEFITS AND LOADS BEYOND THE LIFE CYCLE
Environmental indicators		A1 / A2 / A3	A4 Transport	A5 Installation	B1 Use	B2 Maintenance	B3 Repair	B4 Replacement	B5 Refurbishment	B6 Operational energy use	B7 Operational water use	C1 Deconstruction / demolition	C2 Transport	C3 Waste processing	C4 Disposal	D Reuse, recovery, recycling
	GWP-GHG [kg CO2 eq.] ⁴	4,63E-01	4,80E-02	4,53E-02	-3,22E-02	0	0	0	0	0	0	1,88E-03	7,12E-03	0	1,71E-02	0

⁴ The indicator includes all greenhouse gases included in GWP-total but excludes biogenic carbon dioxide uptake and emissions and biogenic carbon stored in the product. This indicator is thus almost equal to the GWP indicator originally defined in EN 15804:2012+A1:2013.

Information on biogenic carbon content

		PRODUCT STAGE
Biogenic Carbon Content in kg C		A1 / A2 / A3
	Biogenic carbon content in product [kg]	2,53E-03
	Biogenic carbon content in packaging [kg]	7,31E-03

Note: 1 kg biogenic carbon is equivalent to 44/12 kg CO₂.

Additional environmental information:

Electricity information

The factory based in Italy uses the following electricity description.

Parameter	Information
Location	Representative of Electricity purchased by SAINT-GOBAIN ITALIA S.P.A.
Geographical & technical representativeness	Share of energy sources
	Biomass 0,6%
	Hard coal 22,7%
	Heavy fuel oil (HFO) 7,3%
	Lignite 0,1%
	Natural gas 58,2%
	Nuclear 4,4%
	Photovoltaic 6,2%
	Wind 0,4%
	2% transmission losses
Type of dataset/ dataset versions	Sphera CUP2024.2 ecoinvent 3.10 (medium voltage)
Source of electricity mix	AIB report 2024
GWP-GHG CO ₂ eq.	0,683 kg of CO ₂ eq./kWh

Other additional environmental

No additional information displayed

Additional social and economic information

No additional information displayed

Version history

07/07/2026 - Version 1, original version of the EPD

ABBREVIATIONS

DU	Declared unit
EPD	Environmental Product Declaration
eq.	equivalents
FU	Functional unit
g	gram
GJ	Giga Joules (as Net Calorific Value)
GO	Guaranties of origin
GWP	Global warming potential
kg	kilogram
kWh	kilowatt-hour
L	liter
LCA	Life Cycle Assessment
LCI	Life Cycle Inventory Analysis
LCIA	Life Cycle Impact Assessment
MJ	Mega Joules (as Net Calorific Value)
PCR	Product Category Rules
RSL	Reference Service Life (in years)
ton	metric ton

References

1. EN 998-1:2016 Primaryation for mortar for masonry Rendering and plastering mortar
2. EN 15804:2012+A1:2013 - Sustainability of construction works - Environmental product declarations - Core rules for the product category of construction products
3. EN 15804:2012+A2:2019/AC:2021 - Sustainability of construction works - Environmental product declarations - Core rules for the product category of construction products
4. EPD International (2025) General Programme Instructions for the International EPD® System. Version 5.0.1 www.environdec.com.
5. EN 15978 Sustainability of construction works - Assessment of environmental performance of buildings - Calculation method
6. The International EPD System PCR 2019:14 Construction products Version 2.0.1; c-PCR-003 Concrete and concrete elements (EN 16757: 2017)
7. European Chemical Agency, Candidate List of substances of very high concern for Authorization. <https://echa.europa.eu/candidate-list-table>
8. LCA report "2025_2 webertec ripara ultra_LCA report template (PCR 2_0 EPD Int)" - 2026